

PROGRESSA[®] SMART BED SYSTEM

Empower patients and caregivers with in-bed therapies to help get your most critical patients better sooner.



STANDARD FEATURES TO HELP OPTIMIZE PATIENT SAFETY AND IMPROVE CAREGIVER SATISFACTION

- SlideGuard™ Frame Technology
- Patient Controls Backlighting
- FlexAfoot™ Retractable Foot Control
- Advanced MicroClimate® Technology
- 30°/45° Head of Bed Alarm
- In-Bed Scale
- Line Managers
- Three Mode Bed Exit Alarm
- Caregiver Pendant
- Caregiver Foot Controls
- Night Light
- Integrated Oxygen Tank Holder
- Accessory Outlet
- Hands Free Emergency CPR & Trendelenburg
- NaviCare Ready - Local Alarm On/Off
- Point of Care™ Siderails Control
- Both Siderails with Point-of-Care Touch Screen
- Smart Bed Ready (Sidecom Required)
- Obstacle Detect™ System at Both Sides of the Bed
- Drainage Bag Holders
- Four IV Sockets

OPTIONAL FEATURES TO SUPPORT THERAPY-FOCUSED TECHNOLOGIES

- Prevention Surface
- Therapy Surface
- Pulmonary Surface
- Continuous Lateral Rotation Therapy (CLRT)
- Percussion & Vibration Therapy (P&V)
- Nurse Call, Univ TV & Lighting
- Siderail Nurse Call
- Bed Exit Alarm to Nurse Call
- 5th Wheel Steering
- IntelliDrive® Powered Transport Steering
- Transport Shelf
- Wireless Connectivity
- Permanent IV Pole
- Full Chair Egress
- StayInPlace™ Patient Migration Management System
- WatchCare™ Incontinence Management System



Hillrom™

Progressa® Smart Bed System

TECHNICAL SPECIFICATIONS

Total Length	
Foot Section Extended	98" (248.9 cm)
Foot Section Retracted	88" (223.5 cm)
Maximum Width	
Side Rails Down	40.5" (103 cm)
Side Rails Up	40.5" (103 cm)
Maximum Side Rail Height	
Above Sleep Deck	17" (43.2 cm)
Highest Position	
Top of Seat Section to Floor	35.7" (90.7 cm)
Lowest Position	
Top of Seat Section to Floor	16.5" (41.9 cm)
Minimum Underbed Clearance	4.3" (10.9 cm) w/o IntelliDrive® Powered Transport
Standard Caster Size	6" (15.2 cm)
Articulations	
Head Section	0° - 67° 77° with Chair Egress
Thigh Section	0° - 30°
Foot Section	0° - 45°
Trendelenburg Position (maximum)	75° with Chair Egress
Reverse Trendelenburg Position (maximum)	13° 18°

Safe Working Load	650 lb (295 kg)
Maximum Patient Weight	500 lb (227 kg)
C-Arm Clearance	7 - 15" (17.8-38.1 cm)
Cleanability/Infection Control	IPX4
Radiolucent Sleep Deck	Standard 17.7" x 23" (45 cm x 58.5 cm)
Voltages	100/110/115/120/ 127/220/230/240
Mattress	
Prevention Surface	
Mattress Width	35" (88.9 cm)
Mattress Length	84" (213 cm)
Mattress Height	7.1" (18.1 cm)
Mattress Weight	31 lb (14.1 kg)
Therapy Surface	
Mattress Width	35.5" (90.2 cm)
Mattress Length	84" (213 cm)
Mattress Height	8" (20.32 cm)
Mattress Weight	45 lb (20.5 kg)
Pulmonary Surface	
Mattress Width	35.5" (90.2 cm)
Mattress Length	84" (213 cm)
Mattress Height	8" (20.32 cm)
Mattress Weight	48 lb (21.8 kg)

SURFACE & FRAME CONFIGURATION OPTIONS

PROGRESSA® PREVENTION	PROGRESSA® THERAPY	PROGRESSA® PULMONARY
Prevention Surface	Therapy Surface	Choose one: - Pulmonary Surface (CLRT only) - Pulmonary Surface (CLRT & P&V)
Choose one: - Dining Chair® Position - FullChair® Position with Chair Egress - FullChair® Position with Chair Egress and StayInPlace™ Technology	Choose one: - Dining Chair® Position - FullChair® Position with Chair Egress - FullChair® Position with Chair Egress and StayInPlace™ Technology	Choose one: - Dining Chair® Position - FullChair® Position with Chair Egress - FullChair® Position with Chair Egress and StayInPlace™ Technology



hillrom.com

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.